

CONTINENTAL / SPIRALITE®

Ag Spray Hose

Agricultural Spray Hose Family

Since 1948 • Six Florida Locations • Worldwide Shipping



alite®

Distributed by:

Goodyear Rubber Products

goodyearrubberproducts.us

About Spiralite® Ag Spray Hose

Spiralite® agricultural spray hoses are manufactured by Continental and engineered for the demanding conditions of modern farm spray equipment. Premium PVC compounds and advanced reinforcement deliver superior pressure ratings, chemical resistance, and long service life.

Goodyear Rubber Products distributes the full Spiralite line for the US market — standard roll lengths or cut-to-order bulk quantities.

Product	Color	Construction	Max WP	Size Range	Temp Range
Spiralite® 310	Yellow	Woven fabric	570 PSI	1/4"–3/4"	10°F–130°F
Spiralite® 320	Orange	Spiral yarn	560 PSI	3/8"–3/4"	10°F–130°F
Spiralite® 340	Green	Woven fabric	800 PSI	3/8"–1"	10°F–130°F
Spiralite® 410	Clear	PVC braid (FDA)	Varies	1/4"–2"	10°F–130°F

Applications: boom sprayers, orchard mist blowers, chemical transfer, low-pressure irrigation, ag spray system plumbing.

Product Specifications

SPIRALITE® 310 — Yellow Ag Spray Hose

Construction	Temperature	Lengths
PVC cover & tube, woven fabric reinforcement	10°F to 130°F (–12°C to 54°C)	300 ft standard rolls

ID (in)	OD (in)	Max WP (PSI)	Min Bend Rad (in)	Wt (lbs/ft)
1/4"	0.50	570	1.5	0.07
3/8"	0.63	570	2.0	0.10
1/2"	0.78	450	3.0	0.13
5/8"	0.94	400	4.0	0.17
3/4"	1.09	400	5.0	0.21

Best for: Standard boom sprayer lines, chemical tank connections, moderate-pressure field spray.

SPIRALITE® 320 — Orange Ag Spray Hose

Construction	Temperature	Lengths
PVC cover & tube, spiral yarn reinforcement	10°F to 130°F (–12°C to 54°C)	300 ft standard rolls

ID (in)	OD (in)	Max WP (PSI)	Min Bend Rad (in)	Wt (lbs/ft)
3/8"	0.65	560	2.0	0.11

ID (in)	OD (in)	Max WP (PSI)	Min Bend Rad (in)	Wt (lbs/ft)
1/2"	0.80	560	3.0	0.14
5/8"	0.95	500	4.0	0.18
3/4"	1.10	450	5.0	0.22

Best for: Orchard spray, high-flexibility routing, spiral-wound pressure retention.

Product Specifications (continued)

SPIRALITE® 340 — Green High-Pressure Ag Spray Hose

Construction	Temperature	Lengths
Green PVC, heavy-duty woven fabric reinforcement	10°F to 130°F (–12°C to 54°C)	300 ft standard rolls

ID (in)	OD (in)	Max WP (PSI)	Min Bend Rad (in)	Wt (lbs/ft)
3/8"	0.67	800	2.5	0.13
1/2"	0.84	700	3.5	0.17
5/8"	1.00	650	4.5	0.21
3/4"	1.17	600	5.5	0.26
1"	1.50	500	7.0	0.38

Best for: High-pressure boom sprayers, hydraulic spray systems, mist cannons, demanding applications.

SPIRALITE® 410 — Clear FDA/USDA Ag Hose

Construction	Temperature	Lengths
Clear PVC braid — FDA/USDA compliant tube & cover	10°F to 130°F (–12°C to 54°C)	100–300 ft (varies by size)

ID (in)	OD (in)	Max WP (PSI)	Min Bend Rad (in)	Std Length (ft)
1/4"	0.50	150	1.5	300
3/8"	0.63	150	2.0	300
1/2"	0.75	125	3.0	300
3/4"	1.00	100	4.5	300
1"	1.25	100	6.0	100
1-1/4"	1.56	75	7.5	100
1-1/2"	1.84	75	9.0	100
2"	2.38	50	12.0	100

FDA/USDA compliant — food-grade, potable water, certified organic spray. Clear for visual flow inspection.

Ordering & Contact

Goodyear Rubber Products

Available In

Custom Lengths

goodyearrubberproducts.us
US Distributor —
Spiralite®/Continental

100 ft and 300 ft rolls
Bulk quantities available

Cut-to-length welcome
Volume pricing available

Since 1948 • Six Florida Locations • Hose Assembly & Testing • Worldwide Shipping

Specifications subject to change without notice. Verify selection against system pressure, fluid compatibility, and temperature requirements.